L2+ Managed Industrial Switch



Key Features & Highlights

- Input Voltage: DC48~58V for PoE
- Operating Temperature: -40℃~85℃
- Shell: IP40 protection
- Fanless design, low power consumption
- ESD: contact 8KV, air 15KV
- MTBF: 100,000 hours

| Product Overview

The **AgniGate S6024-4X24GP-IGM** is an industrial-grade Layer 2+ managed Ethernet switch engineered for mission-critical deployments in harsh, demanding environments such as intelligent transportation systems, smart surveillance, power substations, and factory automation. Encased in a rugged aluminum enclosure with an IP40 ingress rating, it features a Fanless, low-power thermal design, redundant DC power inputs, and carrier-class surge and EMC immunity.

| Technical Reference

- IEEE 802.3 CSMA/CD method
- IEEE 802.3 af PoE
- IEEE 802.3 at PoE+
- IEEE 802.3x Flow Control
- IEEE 802 Networks
- IEEE 802.3 10Base-T
- IEEE 802.3u 100Base-TX/FX
- IEEE 802.3z Gigabit SX/LX
- IEEE 802.3ab Gigabit 1000T
- IEEE 802.3ae 10GBase-X
- IEEE 802.3ad port trunk with LACP
- IEEE 802.1D Spanning Tree Protocol
- IEEE 802.1w Rapid Spanning Tree Protocol
- IEEE 802.1s Multiple Spanning Tree Protocol
- IEEE 802.1p Class of Service
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.3ah Ethernet Link OAM

- IEEE 802.1p Class of Service
- IEEE 802.1Q VLAN tagging
- IEEE 802.1X Port Authentication Network Control
- IEEE 802.1ab LLDP
- IEEE 802.1ag Connectivity Fault Management(CFM)
- RFC 1112IGMP v1
- RFC 2236 IGMP v2
- RFC 3376IGMP v3
- RFC 2710 MLD v1
- RFC 4604 MLD v2
- RFC783 TFTP
- RFC 791 IP
- RFC 792 ICMP
- RFC 2068 HTTP
- RFC 2616 HTTPS
- ITU-T G.8032 ERPS Ring

| EMC & Protection

- IP Level: IP40
- Surge of Power: IEC 61000-4-5 Level X (6KV/6KV) (1.2/50us)
- Surge of Ethernet port: IEC 61000-4-5 Level 4 (4KV/4KV) (10/700us)
- RS: IEC 61000-4-3 Level 3 (10V/m)
- EFI:IEC 61000-4-4 Level 3 (1V/2V)
- CS: IEC 61000-4-6 Level 3 (10V/m)
- PFMF: IEC 61000-4-8 Level 4 (30A/m)
- DIP:IEC 61000-4-11 Level 3 (10V)
- ESD:IEC 61000-4-2 Level 4 (8K/15K)
- Free fall: 0.5m

| Hardware Specifications

Model	S6024-4X24GP-IGM
Interface	24*10/100/1000M RJ45 ports, 4*10G SFP+ ports
Switching Capacity	128Gbps
Packets Forwarding Rate	101.2Mpps
MAC Table	16K
Packet Buffer	12M
Forwarding Delay	<10us

Power Supply	Phoenix terminal, DC redundant input
	Input Voltage: DC48-58V
	Empty Load Power: <26W
LED Indicators	PWR, NMC, Link/ACT LED
PoE	1-24 ports support PoE
	PoE budget: 386W
	IEEE802.3 af/at standard
	PIN Sequence: 1,2+/3,6-
PoE++	1-2&15-16 ports support PoE++
	PoE budget: 386W
	IEEE802.3 af/at/bt standard
	PIN Sequence: 1245+，3678-
Environment	Working Temperature: –40℃ ~ 85℃
	Storage Temperature: –40℃ ~ 85℃
	Working Humidity: 5%~95% non-condensing
	Storage Humidity: 5%~95% non-condensing
SIZE(W*D*H)	143*104*94mm
Weight	1.03KG
Installation Method	Din Rail
Certificate Compliance	CE/FCC/RoHS
MTBF	100,000 hours


Software Specifications

Model	S6024-4X24GP-IGM
VLAN	Support 4K IEEE 802.1Q VLAN, 802.1ad – QinQ
	Support protocol VLAN
	Support GARP

Model	S6024-4X24GP-IGM
LACP	Support IEEE 802.3ad
	Support static LACP
	Support dynamic LACP
STP	Support IEEE 802.1d STP
	Support IEEE 802.1w RSTP
	Support IEEE 802.1s MSTP
ERPS	Support ITUT G.8032 protocol
Port	Support Jumbo Frame
	Support IEEE802.3X Flow Control
	Support port statistics
	Support Auto-MDI/MDIX
Multicast	Support IGMP Snooping
	Support MVR
ACL	Support MAC Standard/Extended ACL
	Support IPv4 Standard/Extended ACL
	Support IPv6 Standard/Extended ACL
QoS	Support QoS Re-marking
	Support Port Trust
	Support Port Rate Limiting
	Support Egress Queue Rate Limiting
DHCP	Support DHCP Snooping
	Support DHCP Client
	Support DHCP Server
L3 Route	IPv4 Management Address
	IPV6 Management Address
	Static IPv4 Route
	Static IPv6 Route
	ARP
	Loopback Interface
Security	Support IEEE802.1X
	Support MAC-Based IEEE802.1X
	Support WEB-Based IEEE802.1X

Model	S6024-4X24GP-IGM
Security	IP Source Guard
	Port Security
	Port Isolation
Diagnosis	Support Console Logs
	Support RAM logs
	Support Flash logs
	Support Port Mirroring(1:1,N:1)
Diagnosis	Support Ping
	Support Traceroute
	Support Cable Test
	Support Optical Module Information
Management	Support User Management
	Support System Log
	Support Firmware Upgrade
	Support File Upgrade
	Support SNMP
	Support WEB Management
	Support Console
	Support CLI
	Support Telnet/SSH

Product Dimension



AGNIGATE TECHNOLOGIES PRIVATE LIMITED

Corporate Support

Website: www.agnigate.com | Email: support@agnigate.com | 24/7 TAC support Toll Free 1800 572 6097
© 2026 Agnigate Technologies Pvt. Ltd. All rights reserved. Specifications subject to change without prior notice.